



Food processing and packaging equipment

VACUUM PACKAGING MACHINES

Single Chamber Models

400 / 450A / 450T / 550A / 580A

Heavy-duty

This high-quality, user-friendly, and easy to clean machine integrates heavy-duty parts, thereby providing great reliability.

Performance

This model is designed to package large volumes of oversized products. The modified atmosphere packaging (MAP) option extends the shelf life of food and reduces the need for preservation chemicals.

Certifications

The Sipromac vacuum packaging machines are ETL LISTED, CSA certified and conform to UL STD.




Why should you vacuum pack?


- To reduce spoilage by removing air from the package resulting in much longer shelf life;
- To prevent dehydration;
- For ease of handling;
- To slow down oxidation;
- To protect against external contamination.

Seal bars

2 seal bars



Machine dimensions



Model 450T



SINGLE CHAMBER MODELS			400	450A	450T	550A	580A
SEAL BARS	Length	A	19.5" / 496 mm	19.5" / 496 mm	19.5" / 496 mm	25.25" / 642 mm	33.5" / 855 mm
	Quantity		2	2	2	2	2
	Distance between	B	23" / 584 mm	23" / 584 mm	22" / 559 mm	23.25" / 591 mm	36.75" / 933 mm
CHAMBER DIMENSIONS	Height		9.5" / 241 mm	9.5" / 241 mm	8" / 203 mm	8" / 203 mm	8" / 203 mm
BUSCH PUMP	Std. / Option		40 m ³ 2.0 HP	40 m ³ 2.0 HP	20 m ³ 2.0 HP	63 m ³ 3.0 HP	165 m ³ 7.5 HP
MACHINE DIMENSIONS	Width	E	30.5" / 775 mm	30.5" / 775 mm	30.5" / 775 mm	31" / 787 mm	45.25" / 1,153 mm
	Depth	F	32" / 813 mm	32" / 813 mm	28" / 711 mm	36" / 914 mm	46.5" / 1,183 mm
	Height	G	44" / 1,118 mm	44" / 1,118 mm	21" / 533 mm	47" / 1,194 mm	43.75" / 1,113 mm
POWER SUPPLY			208-220 V / 3 pH / 60 Hz	208-220 V / 3 pH / 60 Hz	208-220 V / 3 pH / 60 Hz	208-220 V / 3 pH / 60 Hz	208-220 V / 3 pH / 60 Hz
MICROPROCESSOR			MC-05	MC-40	MC-40	MC-40	MC-40

Basic Features:

- Stainless steel construction
- Vacuum sensor
- Twin seal element
- Filler plates
- Cover latch
- ETL, CSA, UL certification (except model 400)
- NSF certification (450T)

Optional Features:

(Available on selected models)

- Electric cut-off
 - Gas injection system (MAP)*
 - Air regulator – Regulated air pressure in the seal bars bladders with compressed air*
 - Adjustable venting system*
 - 12" (305 mm) vacuum chamber*
 - Top and bottom sealing system*
 - Selection of vacuum pump configurations offered *
 - Multiple supply voltage available
- *On selected models only

All features are subject to change without notice.

MC-05



MC-40



Check out our other products by visiting our website:
www.sipromac.com

Phone: 819 395-5151 | **Toll Free:** 1 855 395-5252 Canada/U.S.
Email: sipromac@sipromac.com
240, boulevard Industriel, Saint-Germain-de-Grantham QC, Canada J0C 1K0

